



Robust Lug Design:

Lug is designed for excellent grip, high traction abilities, low slip, suitable for many kinds of Agro-Forestry uses

Reinforced Sidewall:

Reinforced sidewall and high turn of plies around strong bead to guarantee minimum impact and perforation

Special compound equipped with Steel belt:

To reduce the risk of tire puncture and cut due to branches, tree stumps or stone, AFB 821 tractor tire has **steel belt protection**, strong carcass and **puncture resistant compound** suitable for Agro Forestry work



STEEL BELTED

Size	ALT Size	LI/SI	Ply/*	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)	Psi	Max Speed (mph)
12.4-24 (SB) (CR)	-	130 A8	16	TL	43	W11	135	46	12	137	21	4190	41	25
13.6-24 (SB) (CR)	-	136 A8	16	TL	46	W12	157	48	14	143	22	4930	41	25
14.9-24 (SB) (CR)	-	140 A8	16	TL	43	W13	172	50	15	150	23	5510	41	25
16.9-30 (SB) (CR)	-	149 A8	16	TL	47	W15L	250	59	17	176	27	7160	41	25
18.4-30 (SB) (CR)	-	151 A8	16	TL	48	W16L	286	61	18	184	28	7600	41	25
16.9-34 (SB) (CR))	-	151 A8	16	TL	47	W15L	276	63	17	188	29	7600	41	25
18.4-34 (SB) (CR)	-	155 A8	16	TL	48	W16L	311	65	18	196	30	8540	41	25

(SB) - Steel Belted, (CR) - Cut Resistant