



New generation steer/trailer tire with latest ZC-Rubber PSCT technology for regional application

- Four wide tread grooves allows excellent water drainage
- Multi siping provides outstanding traction on both dry and wet road surfaces
- Computer designed tire casing assures excellent footprint for extended tire life



AZ599

SIZE	LR/PR	SERVICE INDEX	TREAD DEPTH 32nds	STANDARD RIM	OVERALL DIAMETER inch	SECTION WIDTH inch	MAX. LOAD CAPACITY AT COLD INFLATION PRESSURE							
							SINGLE				DUAL			
							kg	lbs	kPa	psi	kg	lbs	kPa	psi
215/75R17.5	H/16	135/133J	16	6.00	30.2	8.3	2180	4805	850	123	2060	4540	850	123
235/75R17.5	H/16	143/141J	16	6.75	31.4	9.2	2725	6005	875	128	2575	5675	875	128
225/70R19.5	G/14	128/126N	16	6.75	31.9	8.9	1800	3970	760	110	1700	3750	760	110
245/70R19.5	H/16	136/134M	18	7.50	33.0	9.8	2240	4940	830	120	2120	4675	830	120
255/70R22.5	H/16	140/137M	18	7.50	36.6	10.0	2500	5510	830	120	2300	5070	830	120
275/70R22.5	H/16	148/145L	18	8.25	37.7	10.9	3150	6940	900	130	2900	6395	900	130
11R22.5	H/16	148/145L	18	8.25	41.5	11.0	3150	6940	850	123	2900	6390	850	123
295/75R22.5	G/14	144/141L	18	9.00	39.9	11.7	2800	6175	760	110	2575	5675	760	110
315/80R22.5	J/18	154/151M	19	9.00	42.4	12.3	3750	8270	830	120	3450	7610	830	120
11R24.5	H/16	149/146L	18	8.25	43.5	11.0	3250	7160	830	120	3000	6610	830	120
285/75R24.5	G/14	144/141L	18	8.25	41.1	11.1	2800	6175	760	110	2575	5675	760	110