



Robust Tread Design:

- Optimum contact area for better stability
- Excellent self-cleaning properties
- Minimum slippage and enhanced traction

Strong Nylon Carcass:

Safeguards the tire against failures

Thick Under Tread:

Ensures protection from cuts and punctures



Size	ALT Size	LI/SI	Ply/*	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)	Psi	Max Speed (mph)
10.5/80-18	-	123 B	12	TL	32	9	67	35	11	104	16	3410	72	31
12.5/80-18	-	142/129A8	12	TL	34	9	91	39	12	114	17	5840	54	25
12.5/80-18	-	145/132A8	14	TL	34	9	96	39	12	114	17	6390	62	25
400/70-20	16.0/70-20	149A8	16	TL	30	13	129	42	16	127	19	7160	59	25
14.9-24	-	145A8	12	TL	32	13	136	49	15	146	22	6390	43	25
16.9-24	-	149A8	12	TL	35	15	163	52	17	154	24	7160	38	25
17.5L-24	-	144A8	10	TL	33	15	154	49	18	146	22	6170	32	25
18.4-24	-	155A8	12	TL	36	15	202	54	19	162	25	8540	37	25
18.4-26	-	156A8	12	TL	36	16	221	56	19	168	26	8810	37	25
18.4-26	-	159A8	14	TL	36	16	224	56	19	168	26	9640	43	25
16.9-28	-	152A8	12	TL	35	15	183	56	17	166	26	7820	38	25
16.9-30	-	153A8	12	TL	35	15	203	58	17	172	27	8040	40	25