



## Strong Carcass for Longer Service:

- Designed for stability while loading and unloading
- Optimum contact area ensures high traction
- Excellent wear resistance in severe conditions



| Size      | ALT Size   | LI/SI      | Ply/* | Type | Tread Depth (32 nds) | Preferred Rim | Wt (lbs) | OD inches | SW inches | RC inches | SLR inches | Max Load (lbs) | Psi | Max Speed (mph) |
|-----------|------------|------------|-------|------|----------------------|---------------|----------|-----------|-----------|-----------|------------|----------------|-----|-----------------|
| 480/80-26 | 18.4-26    | 158 A8     | 14    | TL   | 38                   | DW15L         | 239      | 56        | 19        | 166       | 25         | 9360           | 42  | 25              |
| 340/80-18 | 12.5/80-18 | 142/129 A8 | 12    | TL   | 34                   | 11            | 106      | 40        | 14        | 118       | 18         | 5830           | 54  | 25              |
| 340/80-18 | 12.5/80-18 | 145 A8     | 14    | TL   | 33                   | 11            | 111      | 39        | 14        | 118       | 18         | 6390           | 62  | 25              |
| 340/80-18 | 12.5/80-18 | 148/135 A8 | 16    | TL   | 34                   | 11            | 112      | 40        | 14        | 118       | 18         | 6930           | 71  | 25              |