



NEW PATTERN

Reinforced lug design with longer shoulder:

Ensures excellent traction, stability and less chance of tipping while operating at height

Rim Guard Protector with Extra Heavy-Duty Sidewall:

Safeguards the tire against damages

Extra Strong Casing:

Higher load-carrying capacity in all applications & Improved Stability

Special Rubber compound:

Longer Tire Life-reduced downtime and higher productivity

Optimized inner volume:

- For low tire fill consumption
- Can be filled with foam to eliminate chances of flat



Size	ALT Size	LI/SI	Ply/*	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)	Psi	Max Speed (mph)
15-625	-	168 A2	16	TL	27	15	139	41	15	122	19	12350	100	6
18-625	-	175 A2	16	TL	27	15	156	40.5	17.2	121.5	18.9	15210	100	6
IN315/55D20	-	151 A2	12	TL	25	11	81	33	13	98	15	7610	80	6
IN355/55D625	-	157 A2	14	TL	26	12	102	37	14	111	17	9090	75	6
IN445/50D710	-	177 A2	18	TL	30	15	199	47	17	140	22	16090	100	6