



Unique XAD Pattern:

- Uniform wear
- Less slippage
- Improved fuel efficiency

Specially-designed CCR Compound:

Cut and chip-resistant compound provides excellent resistance to severe terrain conditions



Size	ALT Size	LI/SI	Ply/*	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)	Psi	Max Speed (mph)
16.9-24	-	152A8	14	TL	34	DW 15L	200	52	17.0	155	23	7820	44	25
17.5L-24	-	153A8 152	16	TL	33	DW 15L	186	49	18.0	147	22	8040	48	25
16.9-28	-	A8 156 A8	12	TT	46	DW 15 L	207	56	17.0	166	25	7820	38	25
16.9-28	-	159 A8	14	TL	46	DW 15L	220	56	17.0	166	25	8820	47	25
18.4-26 IND	-		14	TT	37	16	240	57	18.0	170	26	9640	42	25

Size	ALT Size	LI/SI	Ply/*	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)		Psi	Max Speed (mph)
												Free Rolling	Drive Wheel		
12.5/80-18	-	142 A8/129A8	12	TT	35	W9	91	38	12	114	17	5840	4070	54	25
12.5/80-18	-	145 A8/132A8	14	TL	35	W9	240	38	12	114	17	6390	4410	62	25