

PRODUCT DATA SHEET

BOSS SLM 70

Tyre Construction: Bias

Type: Tube Type

Main Applications: Tipper

TRA Code: ML



Salient Features:

Wide Central Rib With Optimized Rib Pattern:

Ensures superior traction and directional control on wet, dry, and uneven off-road surfaces, ideal for heavy-duty steering.

Special Cut and Chip-Resistant Tread Compound:

Offers superior wear resistance while minimizing the risk of cuts and punctures in aggressive mining and construction environments

Reinforced Nylon Casing:

Enhances load-bearing capacity and improves durability under high-stress conditions

Durable Construction with Balanced Tread Design:

Promotes even wear, minimizes rolling resistance, and supports consistent performance across a variety of surfaces



Technical Data



Size	Recomm. Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR & LSI	Inflation	Recommended Load kg (lbs)
		SW	OD				Pressure	Speed kmph (mph)
		mm	mm				bar	90
		inch	inch				psi	56
10.00-20	7.5	286	1085	492	3258	18PR	7.6	2800
		11.3	42.7	19.4	128.3	144G	110	6170
11.00-20	8	300	1120	506	3363	18PR	7.6	3000
		11.8	44.1	19.9	132.4	146G	110	6610

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com