

PRODUCT DATA SHEET

BOSS TS 16

Tyre Construction: Bias

Type: Tube Type

Main Applications: Tractor

TRA Code: F-2



Salient Features:

Excellent Road Grip & steering :

- Wider Center Rib.
- Optimum road contact for ease in steering.

Better stability:

- Horizontal Groves lines.
- Resistance to Puncture & Reduce stone trapping.

High Mileage:

- Horizontal Groves lines.
- Resistance to Puncture & Reduce stone trapping.

High Load Carrying Capacity :

- Robust Nylon Casing.
- With stand high load in service.

Exceptional Durability :

- Special designed CCR Compound.
- Offers resistance to cut & chip in all surfaces which provides extended service life..



Technical Data



Size	Rim	Unloaded Dimension		Static Loaded Radius	Rolling Circumference	PR, LI&SI	Inflation Pressure	Recommend load, kg (lbs)				
		SW	OD					Speed, km/h (mph)				
		mm	mm				10	20	25	30	40	
		inch	inch				7	13	16	19	25	
6.00-16	4.50E	175	755	347	2258	8 PR	4.5	1005	905	771	670	536
		6.9	30	14	89	94 A6	66	2210	1990	1700	1480	1180

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

