



The **CLR 280** is a multi-purpose radial tire designed for telehandlers and compact loaders in agro-industrial applications.

- The wide non-directional tread design offers outstanding traction, control & handling stability on any surface, including industrial application on harder surfaces.
- Steel belt package for enhanced resistance to penetration and durability.
- High Load-bearing capacity is ensured by a robust carcass and a strong bead.
- Special Tread compound offers superior resistance to cuts & chips, increased fuel efficiency, and reduced heat build-up resulting in a longer service life.
- Large center tread blocks contribute to a smoother, more comfortable ride.



## STEEL BELTED

Size	ALT Size	LI/SI	Ply/*	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)	Psi	Max Speed (mph)
365/70R18 (SB)	14.5R18	135 B /146 A2	-	TL	23	11	106	38	14	115	17	4800	54	31
405/70R18 (SB)	16.0/70R18	141 B /153 A2	-	TL	29	13	132	41	16	121	18	5670	54	31
335/80R20 (SB)	12.5R20	136 B /147 A2	-	TL	23	11	111	41	13	124	19	4930	54	31
405/70R20 (SB)	16.0/70R20	143 B /155 A2	-	TL	29	13	140	43	16	127	19	6000	54	31

(SB) - Steel Belted