

- Five ribs with four wide, straight grooves for precise handling and outstanding traction
- Stone rejector platforms prevent stones from lodging in grooves and drilling into belts
- Shallower tread depth helps to resist tread squirm and irregular wear forces for exceptionally long mileage



CR976A

SIZE	LR/PR	SERVICE INDEX	TREAD DEPTH 32nds	STANDARD RIM	OVERALL DIAMETER inch	SECTION WIDTH inch	MAX. LOAD CAPACITY AT COLD INFLATION PRESSURE							
							SINGLE				DUAL			
							kg	lbs	kPa	psi	kg	lbs	kPa	psi
12R22.5	J/18	152/149L	20	9.00	42.7	11.8	3550	7830	930	135	3250	7160	930	135
255/70R22.5	H/16	140/137M	18	7.50	36.6	10.0	2500	5510	830	120	2300	5070	830	120
275/70R22.5	H/16	148/145M	18	8.25	37.7	10.9	3150	6940	900	130	2900	6395	900	130
275/80R22.5	H/16	149/146M	18	8.25	39.8	10.9	3250	7165	850	123	3000	6610	850	123
295/80R22.5	J/18	152/149M	19	9.00	41.1	11.7	3550	7830	900	131	3250	7160	900	131
385/65R22.5	J/18	158L(160K)	20	11.75	42.2	15.3	4250	9370	850	125	-	-	-	-
425/65R22.5	L/20	165K	19	12.25	44.3	16.9	5150	11340	830	120	-	-	-	-