



- Five ribs with four wide, straight grooves for precise handling and outstanding traction
- Decoupling tread design suitable for long-distance travel
- Applicable for steer and free-rolling wheel position



This company manufactures:

- EPA SmartWay verified technologies and/or
- Verified equipment for SmartWay Designated Tractors
- Verified equipment for SmartWay Designated Trailers

As a result, we assist SmartWay partners with meeting their goals of energy efficiency and emissions reductions.

Learn more about ...
SmartWay
www.epa.gov/smartway

CR989

SIZE	LR/PR	SERVICE INDEX	TREAD DEPTH 32nds	STANDARD RIM	OVERALL DIAMETER inch	SECTION WIDTH inch	MAX. LOAD CAPACITY AT COLD INFLATION PRESSURE							
							SINGLE				DUAL			
							kg	lbs	kPa	psi	kg	lbs	kPa	psi
11R22.5	H/1	148/145M	18	8.25	41.5	11.0	3150	6940	850	123	2900	6390	850	123
295/75R22.5	G/14	144/141L	18	9.00	39.9	11.7	2800	6175	760	110	2575	5675	760	110
11R24.5	H/16	149/146L	19	8.25	43.5	11.0	3250	7160	830	120	3000	6610	830	120
285/75R24.5	G/14	144/141L	19	8.25	41.3	11.1	2800	6175	760	110	2575	5675	760	110