



Flotation Tread Design:

Ensures excellent traction and self-cleaning properties

Superior Carcass Construction:

High load-carrying capacity and directional stability

Special Tread Compound:

Longer tire life and puncture resistance

STEEL BELTED



Size	ALT Size	LI/SI	Ply/*	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)	Psi	Max Speed (mph)
500/60-22.5	-	165A8 FR / 161B 153A8 DW / 149B	18	TL	49	16.00 DC	178	46	20	138	21	11330	52	25
550/60-22.5	-	169A8 FR/156A8 DW 165B FR/152B DW	18	TL	48	16.00 DC	238	49	22	146	22	12760	46	25
600/40-22.5	-	173A6 DW 169A8	18	TL	49	20.00 DC	221	42	24	126	19	14300	87	19
600/40-22.5 (SB)	-	175A6 DW 171A8	20	TL	49	20.00 DC	260	42	24	126	19	15180	102	19
600/50-22.5	-	174A6 DW 170A8	18	TL	49	AG20.00	247	46	24	138	21	14740	87	19
650/45-22.5	-	173A6 DW 169A8	18	TL	49	20.00 DC	271	46	25	136	21	14300	87	19
650/45-22.5 (SB)	-	175A6 DW 171A8	20	TL	49	20.00 DC	309	46	25	136	21	15180	102	19
700/40-22.5 (DB)	-	177A6 DW18 173A8	18	TL	44	24.00 DC	276	45	28	133	20	16100	87	19

(SB)- Steel Belted, (DB)- Dual Bead