



SIZES ADDED

- FFB 840 is a bias steel-belted tire, suitable for forestry applications with forwarders and harvesters.
- The unique tread design and lug angle provide high traction and low slip abilities for improved fuel economy.
- Extensive inter-lug space provides
- Excellent self-cleaning properties and functions well with or without tracks, but tracks can be added for more demanding environments.
- The tire is equipped with a reinforced steel belt for increased resistance to punctures and high load-carrying capacity.
- The Reinforced bead area provides resistance to rim slip.
- Large tread width contributes to low soil compaction and driver comfort by providing a wider footprint.
- A Special tread and sidewall compound coupled with robust sidewalls and a high under the tread offers enhanced puncture resistance.



**STEEL BELTED**

Size	ALT Size	LI/SI	Ply/+	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)	Psi	Max Speed (mph)
710/40-22.5 (SB)	-	161A8 HT -161A2\LT -168A2	20	TT	53	AG24.00	351	46	28	138	21	10190	73	25
600/55-26.5 (SB)	-	165A8 HT -165A2\LT -172A2	20	TT	61	AG20.00	430	53	24	159	24	11340	73	25
710/45-26.5 (SB)	-	168A8 HT -168A2\LT -175A2	20	TT	61	AG24.00	486	53	28	159	24	12330	73	25
800/40-26.5 (SB)	-	170A8 HT -170A2\LT -177A2	20	TT	61	AG28.00	538	53	32	159	24	13220	73	25

(SB) - Steel Belted