

PRODUCT DATA SHEET

FFB 841

Tyre Construction: Bias

Type: Tubeless

Main Applications: Forestry Forwarder

TRA Code: LS-2



Salient Features:

Optimized Tread Design:

- Excellent Traction.
- Unique tread design with inter lug-terraces for optimum self-cleaning.
- Effective track compatibility and enhance lateral stability.

Centre Tie Bar

- Minimizes lug shuffling in operation.
- Strong Lug Base.

Reinforced Steel Belts:

- Provides exceptional puncture resistance & Carry High Load capacity.

Designed for tracks:

- A perfect fit with tracks for exceptional grip.

Stubble guard compound equipped with Robust sidewall.

- Protection against sharp objects in operation.

Reinforced Bead Area:

- Better mounting & Resistance to Slip.



Technical Data



Size	Recomm. Rim	Unloaded Dimension		Loaded Static Radius	Rolling Circumference	LI/SI or PR	Inflation Pressure	Recommended load (kg) (lbs)				
								Speed (kmph) (mph)				
		SW	OD					Forestry Service (LT)	Skidder Service (HT)	Road Application		
		mm	mm					10	10	20	30	40
		inch	inch	inch	inch		psi	6	6	16	19	25
710/40-22.5 SB	AG24.00	709	1167	531	3504	24PR 167A8	6.0	6700	5450	6700	5830	5450
		27.9	45.9	20.9	138.0		87	14760	12000	14760	12840	12000

Note: SB-Steel Belted

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ **E:** enquiry@ascensotyres.com ■ **W:** www.ascensotyres.com