

PRODUCT DATA SHEET

FFB 843

Tyre Construction: Bias

Type: Tubeless

Main Applications: Forestry Forwarder

TRA Code: I-3



Salient Features:

Flotation Tread Design:

- Excellent Traction.
- Better Self Cleaning.

Strong Nylon Carcass:

- High Load Carrying Capacity.

Overlap of lugs at centre:

- Provided good Roadability.
- Low Tread wear.
- Smooth Ride.

Optimized Bead Area:

- Minimizes Bead failure in operation.
- Ease of mounting.
- Resistance to Rim slip.

SSR compound (Special Stubble Resistant):

- Longer Tire Life and defense against stubble which provides better protection on field.

Reinforced Steel belts:

- Increased resistance to punctures and a high carrying capacity.



Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circum.	PR & LI/SI	Inflation Pressure	Recommended load (kg) (lbs)										
								Speed (kmph) (mph)										
		SW	OD					Free rolling					Drive Wheel					
		mm	mm					10	25	30	40	50	10	25	30	40	50	
inch	inch	inch	inch	inch	inch	bar	10	25	30	40	50	10	25	30	40	50		
						psi	6	16	19	25	31	6	16	19	25	31		
400/60-15.5 SB	AG 13.00	404	874	395	2625	20 PR	3.7	4170	3550	3340	2980	2680	2940	2500	2350	2100	1890	
							54	9174	7810	7340	6556	5896	6468	5500	5170	4620	4158	
						152 A8 / 148 B FR	4.1	4420	3760	3540	3160	2840	3120	2650	2500	2230	2010	
							59	9724	8272	7790	6952	6248	6864	5830	5490	4906	4422	
			15.9	34.4	15.6	103.3	140 A8 / 135 B DW	4.1	4420	3760	3540	3160	2840	3120	2650	2500	2230	2010
							65	10296	8734	8230	7348	6622	7238	6160	5790	5170	4664	
							5.0	4970	4220	3980	3550	3200	3500	2980	2800	2500	2250	
							73	10934	9284	8750	7810	7040	7700	6556	6160	5500	4950	

Note: SB-Steel Belted

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com