



Unique Block Pattern Design:

- Ensures high traction
- Optimum load distribution and wide footprint for higher stability
- Enhanced performance in both indoor and outdoor areas



Size	ALT Size	LI/SI	Ply/*	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)		Psi
												Load Wheel 9 mph	Steer Wheel 16 mph	
5.00-8	-	-	10	TT	16	3.00D	14	19	5	55	8	2750	-	145
18X7-8	-	-	16	TT	16	4.33R	18	18	7	55	8	4690	3610	145
21X8-9	-	-	14	TT	20	6.00E	29	21	8	63	9	5180	3930	131
6.00-9	-	-	10	TT	17.0	4.00E	20	21	6	64	10	3710	2820	123
6.50-10	-	-	12	TT	18	5.00F	28	24	7	70	11	4740	3600	131
7.00-12	-	-	12	TT	18	5.00S	37	27	8	80	12	5990	4550	125
7.00-12	-	-	14	TT	18	5.00S	41	27	8	80	12	6151	4674	125
7.00-15	-	-	12	TT	20	6.00	46	30	8	90	14	6940	5280	125
7.50-15	-	-	12	TT	20	6.00	56	32	9	95	14	7690	5840	116
8.25-15	-	-	14	TT	23	6.50	68	33	9	100	15	9370	7130	116
300-15	-	-	20	TT	28	8	94	33	12	99	15	14480	10990	131
28X9-15	-	-	14	TT	23	7.00	49	28	9	83	13	7520	5720	145