

PRODUCT DATA SHEET

FLS 692

Tyre Construction: Solid

Type: -

Main Applications: Forklift

TRA Code: NA



Salient Features:

Wide Tread with Continuous Center:

Reduces vibrations, increases life and provides higher mileage.

Special Tread Geometry with Square Shoulders &

Flat Footprint:

Enhances stability & life given. Increased contact area & surface grip.

Special Tyre Construction & Compounding:

Impact/vibration damping & enhanced thermal endurance. Maximum resistance against cracks.

Steel Wire Creed Beads:

Prevents tyre slippage on rim & associated heat built-up. Ensures vehicle uptime.

3 Stage Construction for 16-20 Hrs. Operations/Day.



Technical Data



Size	Rim	Heel		Tyre Dimensions			Tyre Load Capacity on Forklift Trucks at Max speed kg (lbs)	
		Standard	Quick	OD	OW	Wear Limit	Load Wheel	Steer Wheel
				mm	mm	mm	25 kmph	25 kmph
				inch	inch	inch	16 mph	16 mph
15x4.5-8 (125/75-8)	3.00D-8	✓	✓	377	113	29	1040	800
				14.84	4.45	1.14	2293	1764
5.00-8	3.00D-8	✓	✓	453	118	43	1415	1090
				17.83	4.65	1.69	3120	2403
18x7-8 (180/70-8)	4.33R-8	✓	✓	452	155	50	2145	1650
				17.8	6.1	1.97	4729	3638
140/55-9 (15x5.5-9)	4.00E-09	✓	✓	376	130	31	1170	900
				14.8	5.12	1.22	2579	1984
6.00-9	4.00E-09	✓	✓	523	134	57	1885	1450
				20.6	5.3	2.24	4156	3197
21X8-9 (200/75-9)	6.00E-09	✓	✓	515	183	52.5	2755	2120
				20.28	7.2	2.07	6074	4674
6.50-10	5.00F-10	✓	✓	566	158	64	2340	1800
				22.28	6.22	2.52	5159	3968
7.00-12	5.00S-12	✓	✓	648.5	171	62.25	2920	2240
				25.53	6.73	2.45	6437	4938
250-15 (250/70-15)	7.0-15	✓	✓	716	220	66	4745	3650
				28.19	8.66	2.6	10461	8047
250-15 (250/70-15)	7.5-15	✓	✓	716	220	66	4745	3650
				28.19	8.66	2.6	10461	8047
28X9-15 (8.15-15) (225/75-15)	7.0-15	✓	✓	685	223	60	3900	3000
				26.97	8.78	2.36	8598	6614
8.25-15	6.5-15	✓	✓	806	208	77	4615	3550
				31.73	8.19	3.03	10174	7826
300-15 (315/70-15)	8.0-15	✓	✓	812	252	82	5850	4500
				31.97	9.92	3.23	12897	9921

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com