



Optimized Flotation Design:

- Reduces soil compaction
- Generates traction
- Self-cleaning properties

Enhanced Carcass Construction:

Ensures high load-carrying capacity



Size	ALT Size	LI/SI	Ply/*	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)	Psi	Max Speed (mph)
400/60-15.5	-	145A8 F.R.	14	TL	23	AG13.00	75	34	16	103	16	6380	52	25
400/60-15.5	-	148A8 F.R.	16	TL	23	AG13.00	78	34	16	103	16	6930	61	25
400/60-15.5	-	151A8 F.R.	18	TL	23	AG13.00	82	35	16	103	16	7590	73	25
500/50-17	-	149 A8 F.R.	14	TL	16	16	121	37	20	110	17	7150	41	25
500/50-17	-	157 A8 F.R.	18	TL	16	16	129	37	20	110	17	9075	58	25
400/55-22.5	-	150 A8 F.R.	14	TL	24	13	108	40	16	120	19	7370	44	25
400/55-22.5	-	152 A8 F.R.	16	TL	24	13	109	40	16	120	19	7810	58	25
550/45-22.5	-	159 A8 F.R.	16	TL	32	16	160	42	22	126	19	9625	41	25
550/45-22.5	-	159 A8 F.R.	20	TL	32	16	177	42	22	126	19	11660	51	25
500/45-22.5	-	154A8 F.R.	16	TL	32	16	155	40	20	120	19	8250	52	25
500/50-22.5	-	163 A8 F.R.	20	TL	28	AG16.00	160	42	20	127	19	10730	55	25
500/60-22.5	-	163 A8 F.R.	16	TL	33	16	196	46	20	138	21	10725	46	25
500/60-22.5	-	170 A8 F.R.	20	TL	33	16	184	46	20	138	21	13200	73	25
550/60-22.5 V	-	166 A8 F.R.	16	TL	33	16	196	49	22	146	22	11660	44	25
550/60-22.5	-	166 A8 F.R.	16	TL	33	16	196	49	22	146	22	11660	44	25
550/60-22.5	-	171 A8 F.R.	20	TL	33	16	231	49	22	146	22	13530	51	25
600/50-22.5	-	165 A8 F.R.	16	TL	32	20	245	46	24	138	21	11330	41	25
600/55-22.5	-	169 A8 F.R.	16	TL	33	20	231	49	24	145	22	12760	38	25
600/55-26.5	-	170 A8 F.R.	16	TL	33	20	259	52	24	157	24	13200	38	25
700/40-22.5	-	166 A8 F.R.	16	TL	33	24	240	45	29	134	21	11660	38	25
700/50-22.5	-	174 A8 F.R.	16	TL	33	20	273	50	29	150	23	14740	41	25
700/50-26.5	-	174 A8 F.R.	16	TL	33	20	297	52	29	157	24	14740	35	25
800/45-26.5	-	177 A8 F.R.	16	TL	33	24	338	55	33	164	25	16060	32	25