



Steel Belted Directional Tread for Superior Traction:

- Homogenous pattern for on-road and farm applications
- Tires designed for high load and speed operations
- Ensure traction and self-cleaning during field operation
- Enhanced roadability and better mileage



STEEL BELTED

Size	ALT Size	LI/SI	Ply/*	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)	Psi	Max Speed (mph)
500/50R17 (SB)	-	149 D	-	TL	20	16.00	141	37	20	110	17	7160	73	40
560/45R22.5 (SB)	-	152 D	-	TL	28	AG16.00	199	42	21	127	19	7820	58	40
600/50R22.5 (SB)	-	159 D	-	TL	28	AG20.00	243	46	24	138	21	9645	58	40
620/40R22.5 (SB)	-	154 D	-	TL	28	AG20.00	226	42	25	126	19	8260	58	40
500/60R22.5 (SB)	-	155 D	-	TL	28	AG16.00	212	46	20	139	21	8540	58	40
560/60R22.5 (SB)	-	164 D	-	TL	28	AG16.00	260	49	21	147	22	11010	73	40
750/45R26.5 (SB)	-	170 D	-	TL	31	AG24.00	363	53	30	159	24	13220	58	40
710/50R26.5 (SB)	-	170D	-	TL	31	AG20.00	375	54	29	163	25	13228	58	40
600/55R26.5 (SB)	-	165D	-	TL	31	AG20.00	307	52	24	157	24	11354	58	40
650/55R26.5 (SB)	-	170 D	-	TL	31	AG20.00	340	55	25	164	25	13220	58	40
650/55R26.5 (SB)	-	178 D	-	TL	31	AG20.00	390	55	26	164	25	16520	87	40
650/60R26.5 (SB)	-	180 D	-	TL	31	AG20.00	390	57	26	171	26	17620	87	40
800/45R26.5 (SB)	-	174 D	-	TL	33	AG28.00	393	55	33	165	25	14760	58	40
710/50R30.5 (SB)	-	176 D	-	TL	33	AG20.00	414	58	27	175	27	15640	64	40
750/60R30.5 (SB)	-	181 D	-	TL	33	AG24.00	528	66	30	197	30	18170	58	40
850/50R30.5 (SB)	-	182 D	-	TL	33	AG28.00	545	64	34	192	29	18720	58	40

(SB) - Steel Belted