



Optimum Implement Design:

Minimizes soil compaction and protects the grassland

Strong Nylon Carcass:

Provides high load-carrying capacity



| Size | ALT Size | LI/SI | Ply/* | Type | Tread Depth (32 nds) | Preferred Rim | Wt (lbs) | OD inches | SW inches | RC inches | SLR inches | Max Load (lbs) | Psi | Max Speed (mph) |
|--------------|-------------|-----------|-------|------|----------------------|---------------|----------|-----------|-----------|-----------|------------|----------------|-----|-----------------|
| 10.0/80-12 | - | 121/109A8 | 10 | TL | 13 | 9 | 33 | 28 | 10 | 84 | 13 | 3190 | 57 | 25 |
| 10.0/75-15.3 | 260/70-15.3 | 123/111A8 | 10 | TL | 11 | 9 | 32 | 30 | 10 | 90 | 14 | 3410 | 57 | 25 |
| 10.0/75-15.3 | 260/70-15.3 | 130/118A8 | 14 | TL | 11 | 9 | 33 | 30 | 10 | 90 | 14 | 4180 | 80 | 25 |
| 10.0/75-15.3 | 260/70-15.3 | 135/122A8 | 18 | TL | 11 | 9 | 44 | 30 | 10 | 90 | 14 | 4800 | 103 | 25 |
| 11.5/80-15.3 | - | 131/119A8 | 10 | TL | 11 | 9 | 41 | 33 | 11 | 100 | 15 | 4290 | 49 | 25 |
| 11.5/80-15.3 | - | 139/126A8 | 14 | TL | 11 | 9 | 42 | 33 | 11 | 100 | 15 | 5346 | 69 | 25 |
| 11.5/80-15.3 | - | 141/128A8 | 16 | TL | 11 | 9 | 42 | 33 | 11 | 100 | 15 | 5665 | 78 | 25 |
| 11.5/80-15.3 | - | 144/132A8 | 18 | TL | 11 | 9 | 50 | 33 | 12 | 100 | 15 | 6160 | 91 | 25 |
| 12.5/80-15.3 | 300/80-15.3 | 142/129A8 | 14 | TL | 11 | 9 | 53 | 34 | 12 | 102 | 15 | 5830 | 62 | 25 |
| 12.5/80-15.3 | | 151/139A8 | 18 | TL | 11 | 9 | 62 | 34 | 12 | 102 | 15 | 7590 | 98 | 25 |
| 10.5/65-16 | - | 130/118A8 | 14 | TL | 10 | W9 | 37 | 30 | 11 | 89 | 14 | 4180 | 77 | 25 |
| 13.0/75-16 | - | 138A8 | 12 | TL | 15 | 11 | 63 | 35 | 13 | 106 | 16 | 5190 | 52 | 25 |
| 10.5/80-18 | - | 138A8 | 14 | TL | 14 | W9 | 54 | 35 | 11 | 104 | 16 | 5190 | 75 | 25 |
| 12.5/80-18 | - | 148/135A8 | 16 | TL | 15 | 9 | 75 | 38 | 12 | 114 | 17 | 6930 | 71 | 25 |
| 13.0/65-18 | - | 144/131A8 | 16 | TL | 15 | 11 | 68 | 35 | 13 | 105 | 16 | 6160 | 71 | 25 |
| 15.0/70-18 | - | 151/139A8 | 16 | TL | 15 | 13 | 93 | 39 | 15 | 117 | 18 | 7590 | 62 | 25 |