



**Wider Footprint:**

Minimizes soil compaction and protects the grassland

**Optimum Height to Width Ratio:**

Ensures stability

**Strong Nylon Carcass:**

Provides high load-carrying capacity



Size	ALT Size	LI/SI	Ply/*	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)	Psi	Max Speed (mph)
260/70-15.3	-	122/110 A8	10	TL	14	9	37	30	11	89	14	3300	46	25
260/70-15.3	-	131/119 A8	14	TL	14	9	40	30	11	89	14	4290	73	25
300/80-15.3	-	139 A8	14	TL	13	9	51	34	12	102	15	5346	54	25
400/60-15.5	-	148/135 A8	16	TL	15	13	74	34	16	103	16	6930	61	25
400/60-15.5	-	145/132 A8	14	TL	15	13	73	34	16	103	16	6380	52	25
400/60-15.5	-	149/136 A8	18	TL	15	13	77	34	16	103	16	7150	65	25
340/55-16	-	133/121 A8	12	TL	15	11	49	31	14	92	14	4532	46	25
340/55-16	-	140/128 A8	18	TL	15	11	53	31	14	92	14	5500	70	25
380/55-17	15.0/55-17	134/122 A8	10	TL	15	13	60	33	15	100	15	4664	38	25
380/55-17	15.0/55-17	141/128 A8	14	TL	15	13	57	33	15	100	15	5665	46	25
380/55-17	15.0/55-17	146/134 A8	18	TL	15	13	73	33	15	100	15	6600	67	25
480/45-17	19.0/45-17	146/134 A8	14	TL	17	16	88	34	19	102	16	6600	46	25
480/45-17	19.0/45-17	149/136 A8	18	TL	17	16	96	34	19	102	16	7150	51	25
500/50-17	-	143/131 A8	10	TL	17	16	111	37	20	110	17	5995	29	25
500/50-17	-	149/137 A8	14	TL	17	16	121	37	20	110	17	7150	41	25
500/50-17	-	154/142 A8	18	TL	17	16	116	37	20	110	17	8250	58	25
500/55-20	-	150/138 A8	10	TL	17	16	116	42	20	125	19	7370	35	25
500/55-20	-	155/143 A8	12	TL	17	16	129	42	20	125	19	8525	46	25
400/70-20	16.0/70-20	156/144 A8	16	TL	15	13	107	42	16	126	19	8800	58	25