



Specially Designed Ribbed Tire:
Low rolling resistance

Wider Center Rib:
Provides excellent Maneuverability and long tire life

Constant Tension Construction
Minimizes Crowning of the Tire



Size	ALT Size	LI/SI	Ply/*	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)	Psi	Max Speed (mph)
9.5L-14 SL	-	111 B	8	TL	10	8	30	29	10	88	13	2400	44	31
7.60-15 SL	-	110 B	10	TL	8	6	28	29	8	87	13	2320	62	31
9.5L-15SL	-	112 B	8	TL	10	7	31	30	9	90	14	2470	44	31
9.5L-15 SL	-	121 B	12	TL	10	7	38	30	9	90	14	3200	64	31
11L-15 SL	-	113 B	8	TL	10	8	33	31	11	91	14	2540	36	31
11L-15 SL	-	121 B	12	TL	10	8	40	31	11	91	14	3200	52	31
12.5L-15 SL	-	127 B	12	TL	11	10	48	32	13	97	15	3860	52	31
12.5L-16 SL	-	130 B	14	TL	11	10	52	33	13	100	15	4180	56	31
16.5L-16.1	-	141 B	12	TL	14	14	98	40	17	121	18	5675	40	31
21.5L-16.1	-	152 B	14	TL	15	18	141	45	22	133	20	7820	36	31