

PRODUCT DATA SHEET

IMB 168

Tyre Construction: Bias

Type: Tube Less

Main Applications: Implements

TRA Code: I-1

Salient Features:

Specially Designed Rib Tire:

- Five-rib design for increased stability in field & road.

Deeper Tread Groove:

- Provides easy steering machinery equipment.

D.O.T. approved for highway speeds:

- For intermittent highway use on farm implements and wagons in agricultural service.
- Ideally for use in towed implement applications.

Superior Carcass Construction:

- High load-carrying capacity at high speed and excellent tyre life.



Technical Data



Size	Rim	Unloaded Dimension		LSR	RC	PR & LI/SI	Infl. Press.	Recomm. Load	Speed
		SW	OD						
		mm	mm						
		in	in						
9.5L-15 FI	7	241	767	350	2294	12 PR 123J	6.2	1550	100
		9.4	30.2	13.8	90.3		90	3420	62
11L-15 FI	8LB	279	777	354	2324	12 PR 128J	6.2	1800	100
		10.9	30.6	13.9	91.5		90	3960	62
12.5L-15 FI	10LB	318	823	373	2461	12 PR 134J	6.2	2120	100
		12.5	32.4	14.7	96.9		90	4680	62

Note: All tyres confirm to ETRTO standards.

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com