



**NEW PATTERN**

## Multi-block tread design with Wider footprint:

- Tread design gives wider footprint and gives excellent grip on/off road application even winter condition.
- Offset shoulder block design gives stable and comfortable driving response both ON/OFF road.

## Unique Center Lug:

Provides Stability and a smooth, comfortable ride on hard surfaces, soft conditions even in mud and snow.

## High number of blocks with high rubber-to-void ratio:

Provides low tire vibration and stable ride.

## Extra Strong Casing Equipped with Steel Belts:

Higher load-carrying capacity in all applications & Improved Puncture resistance.

## Special Tread Compound:

Longer Tire Life and provides even wear both on the road and in the field.



**STEEL BELTED**

Size	ALT Size	LI/SI	Ply/*	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)	Psi	Max Speed (mph)
400/80R24 (SB)	14.9R24	149A8/144D	-	TL	34	DW13	192	49	16	147	22	7165	46	40
440/80R24 (SB)	16.9R24	154A8/149D	-	TL	34	DW14L	222	52	17	155	23	8267	46	40
400/80R28 (SB)	14.9R28	151A8/146D	-	TL	34	DW13	215	53	16	159	24	7606	46	40
440/80R28 (SB)	16.9R28	156A8/151D	-	TL	34	DW14L	244	56	17	167	25	8819	46	40
480/65R28 (SB)	-	154A8/149D	-	TL	35	DW15L	235	53	19	157	24	8267	46	40
540/65R28 (SB)	-	160A8/155D	-	TL	35	DW18L	281	56	21	166	25	9921	46	40
440/80R30 (SB)	16.9R30	157A8/153D	-	TL	35	DW14L	257	58	17	173	26	9094	46	40
440/80R34 (SB)	16.9R34	159A8/155D		TL	35	DW14L	285	62	17	185	28	9645	46	40
480/80R34 (SB)	18.4R34	164A8/159D		TL	37	DW15L	332	64	19	192	30	11023	46	40
480/80R38 (SB)	18.4R38	166A8/161D		TL	37	DW15L	368	68	19	204	32	11685	46	40

SB- Steel Belted