



Robust Design: Steel Belted

- Improved tread design- Provides better traction
- Enhanced carcass- Stability for both on and off-road operations
- Excellent self-cleaning properties
- Steel-belted construction for longer tire life



STEEL BELTED

Size	ALT Size	LI/SI	Ply/*	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)	Psi	Max Speed (mph)
340/80R18(SB)	12.5R18	143 A8/B	-	TL	40	11	127	39	14	118	18	6000	58	31
400/70R20(SB)	16.0/70R20	149 A8/B	-	TL	44	13	152	42	16	126	19	7165	58	31
400/80R24(SB)	14.9R24	162 A8/B	-	TL	48	W13	211	49	16	147	22	4750	73	31
440/80R24(SB)	16.9R24	168 A8/B	-	TL	48	DW14L	252	52	17	155	23	5600	73	31
460/70R24(SB)	17.5LR24	159 A8/B	-	TL	49	DW15L	223	49	18	148	22	9640	58	40
500/70R24(SB)	19.5LR24	164 A8/B	-	TL	49	DW16L	251	52	20	154	23	11010	58	40
480/80R26(SB)	18.4R26	167 A8/B	-	TL	48	DW15L	288	56	19	168	25	12000	58	40
440/80R28(SB)	16.9R28	156 A8/B	-	TL	48	DW14L	265	56	17	167	25	8810	46	40

(SB)- Steel Belted