



Specially Designed for Multi-Purpose Applications:

- Wider center lug for comfort & smooth ride
- Designed for better grip & traction
- Increased carcass strength for durability



Size	ALT Size	LI/SI	Ply/*	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)	Psi	Max Speed (mph)
10.0/75-15.3	-	135A8 FR	18	TL	25	9	57	30	10	90	14	4800	103	25
11.5/80-15.3	-	143A8 FR	18	TL	25	9	71	33	11	100	15	6000	87	25
10.5-18	-	130 G	12	TL	25	9	69	36	11	107	16	4190	65	56
12.5-18	-	131 G	12	TL	25	11	95	39	13	117	18	4300	51	56
18-19.5	-	160B	16	TL	32	14	164	43	18	129	20	9920	87	31
18-19.5	-	165B	18	TL	32	14	178	43	18	129	20	11360	105	31
10.5-20	-	131 G	12	TL	27	9	78	38	11	112	17	4300	62	56
12.5-20	-	143B	16	TL	26	11	109	41	13	122	19	6010	65	31
12.5-20	-	132 G	12	TL	27	11	104	41	13	122	19	4410	51	56
14.5-20	-	139 G	14	TL	32	11	129	43	14	129	20	5350	51	56
16.0/70-20	-	145 G	14	TL	32	13SDC	145	42	16	127	19	6390	51	56