



**U.S.A**

# SRW<sup>®</sup> TRAILER WHEELS

SRW P/N	Wheel Size	Nut Holes	P.C.D (in)	C.B.D (in)	Hand Hole	Offset (in)	MAX.Load (lbs)	Qty/40HQ (pcs)
3124013	12x4.0 J	5	4.5"	2.95"	8 Spoke	0	1520	3564
3124014	12x4.0 J	5	4.5"	3.19"	8 Mod	-0.5"	1520	3564
3124015	12x4.0 J	5	4.5"	2.95"	8 Mod	0	1520	3564
3124021	12x4.0 J	4	4"	2.81"	8 Spoke	0	1520	3564
9134511	13x4.5J	5	4.5"	3.19"	8 Spoke	0	1730	2700
9134513	13x4.5J	5	4.5"	3.19"	10Mod	0	1730	2700
9145511	14x5.5J	5	4.5"	3.19"	8Spoke	0	2205	2240
9145510	14x5.5J	5	4.5"	3.19"	10 Mod	0	2205	2240
9155020	15x5J	5	5"	3.31"	10 Mod	0	2160	2160
9155021	15x5J	5	5"	3.19"	10 Mod	0	2160	2160
9155023	15x5J	5	5"	3.19"	8 Spoke	0	2160	2160
9155010	15x5J	5	4.5"	3.31"	10 Mod	0	2160	2160
9155012	15x5J	5	4.5"	3.31"	8Spoke	0	2160	2160
9155011	15x5J	5	4.5"	3.19"	10Mod	0	2160	2160
9155013	15x5J	5	4.5"	3.19"	8Spoke	0	2160	2160
9156011	15x6J	5	4.5"	3.31"	8Spoke	0	2860	1872
9156012	15x6J	5	4.5"	3.19"	8 Spoke	0	2860	1872
9156013	15x6J	5	4.5"	3.19"	10 Mod	0	2860	1872
9156030	15x6J	6	5.5"	4.25"	10Mod	0	2860	1872
9156031	15x6J	6	5.5"	4.25"	8Spoke	0	2860	1872
9166060	16x6K single	6	5.5"	4.25"	10 Mod	0	3640	1440
9166061	16x6K single	6	5.5"	4.25"	8Spoke	0	3640	1440
9166042	16x6K single	8	6.5"	4.88"	10 Mod	0.51"	4080	1440
9166043	16x6K single	8	6.5"	5.15"	10 Mod	0.51"	4080	1440
9166044	16x6K single	8	6.5"	4.9"	10 Mod	0	4080	1440
9166045	16x6K single	8	6.5"	4.9"	8 Spoke	0	4080	1440
3166054	16X6K dual	8	6.5"	4.88"	4oval	5.51"	3500	1180
3166055	16X6K dual	8	6.5"	4.77"	4oval	5.51"	3500	1180
31767A0	17.5x6.75 single	8	6.5"	4.76"	(solid disc)	-0.51"	6005	780
31767A4	17.5x6.75 single	8	6.5"	4.76"	(solid disc)	-0.31"	6005	780
31767A7	17.5x6.75 single	8	6.5"	4.76"	(solid disc)	0.197"	6005	780
31767A9	17.5x6.75 single	8	6.5"	4.76"	8-Round	0.5"	6005	800
31767B1	17.5x6.75 single	8	6.5"	4.76"	(solid disc)	0.5"	6005	800
31767B2	17.5x6.75 single	8	6.5"	4.76"	8-Round	-0.31"	6005	800
31767B3	17.5x6.75 single	8	6.5"	4.76"	8-Round	0.197"	6005	800
31767B4	17.5x6.75 single	8	6.5"	4.76"	8-Round	-0.51"	6005	800
31767B6	17.5x6.75 single	8	6.5"	4.76"	(solid disc)	-0.197"	6005	780
31767B8	17.5x6.75 single	8	6.5"	4.76"	8-Round	0.079"	6005	800
31767B9	17.5x6.75 single	8	6.5"	4.88"	8-Round	0"	6005	800
31767A1	17.5x6.75 dual	8	6.5"	4.76"	2-Ellipse	5.59"	6005	640
3176743	17.5x6.75 dual	8	275mm	8.7"	4-Ellipse	5.59"	6200	720
3176759	17.5x6.75 dual	10	222.25"	6.5"	2-Ellipse	6.18"	6200	680

Promoting World-class Quality Steel And Aluminum Wheel

**U.S.A**

## SRW<sup>®</sup> TRUCK WHEELS

SRW P/N	Wheel Size	Nut Holes	Nut Dia. (mm)	Pilot Type	P.C.D (mm)	C.B.D (mm)	Hand Holes	Disc Thickness	Offset (mm)	MAX.Load (lbs)	Weight (lbs)	Qty/40HQ (pcs)
9228228	22.5x8.25	10	Φ26	HUB	Φ285.75	Φ220	2	11.0mm	168	7400	69	580
8228218	22.5x8.25	10	Φ32	STUD	Φ285.75	Φ222	2	11.0mm	168	7400	69	580
9228226	22.5x8.25	10	Φ26	HUB	Φ285.75	Φ220	5	11.0mm	168	7400	67	580
8228219	22.5x8.25	10	Φ32	STUD	Φ285.75	Φ222	5	11.0mm	168	7400	66.5	580
3248229	24.5x8.25	10	Φ26	HUB	Φ285.75	Φ220	2	11.0mm	169	7400	84.5	480
8248219	24.5x8.25	10	Φ32	STUD	Φ285.75	Φ222	2	11.0mm	169	7400	84	480
5248224	24.5x8.25	10	Φ26	HUB	Φ285.75	Φ220	5	11.0mm	169	7400	83	480
5248214	24.5x8.25	10	Φ32	STUD	Φ285.75	Φ222	5	11.0mm	169	7400	82.4	480
3176747	17.5x6.75 dual	8	Φ26	HUB	Φ275	Φ221	4	11.75mm	142	6200	25.99	720
3196742	17.5x6.75 dual	8	Φ24	HUB	Φ275	Φ221	4	11.0mm	142	5500	29.83	640

## SRW<sup>®</sup> DEMOUNTABLE RIMS

SRW P/N	Wheel Size	Nut Holes	Nut Dia. (mm)	Pilot Type	P.C.D (mm)	C.B.D (mm)	Hand Holes	Disc Thickness	Offset (mm)	MAX.Load (lbs)	Weight (lbs)	Qty/40HQ (pcs)	
4228205	22.5x8.25	Demountable Rims							5.5mm	121	7400	68	580
4248200	24.5x8.25	Demountable Rims							6.0mm	121	7400	78.3	480

## SRW<sup>®</sup> FORGED ALUMINUM WHEEL

SRW P/N	Wheel Size	Nut Holes	Nut Dia. (mm)	Pilot Type	P.C.D (mm)	C.B.D (mm)	Hand Holes	Offset (mm)	MAX.Load (lbs)	Weight (lbs)	Qty/40HQ (pcs)
A228227	22.5x8.25	10	26	HUB	Φ285.75	Φ220	10	168.5	8000	46	532
A248221	24.5x8.25	10	26	HUB	Φ285.75	Φ220	10	169	8000	56.4	486
A229021	22.5x9.00	10	26	HUB	Φ285.75	Φ220.1	10	176.5	10000	54.6	532
A2290P1	22.5x9.00	10	30.5	STUD	Φ285.75	Φ221.1	10	176.5	10000	54.6	532
A2290P0	22.5x9.00	10	30.5	STUD	Φ285.75	Φ221.1	10	79 (inset)	10000	56.7	475
A229003	22.5x9.00	10	26	HUB	Φ335	Φ281.2	10	176.5	9090	52.5	475
A221420	22.5x14.00	10	26	HUB	Φ285.75	Φ220	10	0	12800	73	418
A176060	17.5x6.00	6	21	HUB	Φ205	Φ160.3	6	127	4000	25.7	1100
A176740	17.5x6.75	8	24.5	HUB	Φ275	Φ221.1	8	141	5510	32.7	1004
A176750	17.5x6.75	10	26.75	HUB	Φ225	Φ176	10	141	5550	32.3	1004
A1767N1	17.5x6.75	8	17.4	HUB	Φ165.1	Φ121	8	21	6050	27.77	1004
A1767N2	17.5x6.75	8	17.4	HUB	Φ165.1	Φ121	8	141	6200	33.73	1004