



**Deep Tread and Optimized Spaced Lugs:**

Ensures high traction and improves self-cleaning abilities

**Extra Strong Casing:**

Higher load-carrying capacity in all applications

**Special Tread Compound:**

High tear and cut resistance in loading operations



Size	ALT Size	LI/SI	Ply/*	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)	Psi	Max Speed (mph)
23x8.50-12	-	87A8	8	TL	18	7	26	23	8	68	10	1200	49	25
26x12.00-12	-	114A8	12	TL	24	11	46	26	12	77	12	2600	78	25
27x8.50-15	-	102A8	8	TL	18	7	33	27	8	80	12	1870	61	25
27x10.50-15	-	105A8	8	TL	19	8.5	38	27	10	81	13	2040	61	25
31x15.50-15	-	125A8	10	TL	24	13	69	31	15	93	14	3640	61	25
33x15.50-16.5	-	148A2	12	TL	29	12	95	33	16	99	15	6940	59	6
10-16.5	-	130A2	8	TL	27	8	52	30	10	91	14	4140	60	6
10-16.5	-	134A2	10	TL	27	8	53	30	10	91	14	4710	75	6
12-16.5	-	140A2	10	TL	29	10	75	33	12	91	14	5600	65	6
12-16.5	-	145A2	12	TL	29	10	78	33	12	91	14	6393	80	6
14-17.5		155A2	14	TL	30	11	121	36	14	108	16	8543	80	6
15-19.5		146A8	14	TL	32	12	134	40	16	120	18	6600	70	25