



SIZES ADDED

Wider Lugs:

Easy to penetrate the soil, generate optimum traction and ensure comfortable ride

Sturdy Sidewall Structure:

Provides resistance to external damage

Strong Nylon Carcass:

Safeguards the tire against failures



Size	ALT Size	LI/SI	Ply/*	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)	Psi	Max Speed (mph)
8-16	-	88 A8	6	TT	35	6LB	32	31	8	93	14	1230	28	25
8.3-20	-	92 A8	6	TT	35	W6	40	35	8	105	16	1390	35	25
9.5-20	-	99 A8	6	TT	35	W8	46	37	9	111	17	1710	30	25
11.2-20	-	107 A8	8	TT	42	W10	65	39	11	118	18	2150	35	25
8.3-24	-	105 A8	8	TT	35	W7	44	39	8	117	18	2040	45	25
9.5-24	-	112 A8	8	TT	39	W8	57	41	9	123	19	2470	41	25
11.2-24	-	116 A8	8	TT	42	W10	70	43	11	130	20	2750	36	25
11.2-24	-	124 A8	12	TT	42	W10	79	43	11	130	20	3520	52	25
12.4-24	-	121A8	8	TT	43	W11	86	46	12	136	21	3190	32	25
12.4-24	-	128 A8	12	TT	43	W11	96	46	12	136	21	3960	49	25
13.6-24	-	123 A8	8	TT	45	W12	103	48	14	142	22	3410	28	25
13.6-24	-	130 A8	12	TT	45	W12	114	48	14	142	22	4190	42	25
14.9-24	-	128 A8	8	TT	43	W13	119	50	15	149	23	3960	26	25
14.9-24	-	136 A8	12	TT	43	W13	139	50	15	149	23	4930	38	25
16.9-24	-	133 A8	8	TT	47	W15L	148	52	17	157	24	4540	24	25
16.9-24	-	143 A8	12	TT	47	W15L	167	52	17	157	24	6000	35	25
14.9-26	-	129 A8	10	TT	45	W13	140	52	15	155	24	4070	32	25
16.9-26	-	133 A8	10	TT	48	W15L	166	54	17	163	25	4540	28	25
11.2-28	-	118 A8	8	TT	42	W10	80	47	11	142	22	2910	36	25
12.4-28	-	123 A8	8	TT	43	W11	98	50	12	148	23	3410	32	25
12.4-28	-	131 A8	12	TT	43	W11	110	50	12	148	23	4300	51	25
13.6-28	-	125 A8	8	TT	45	W12	114	52	14	154	24	3630	28	25
14.9-28	-	130 A8	8	TT	47	W13	132	54	15	161	25	4190	26	25
14.9-28	-	137 A8	12	TT	47	W13	148	54	15	161	25	5070	38	25
16.9-28	-	135 A8	8	TT	47	W15L	160	56	17	169	26	4800	24	25
16.9-28	-	143 A8	12	TT	47	W15L	172	56	17	169	26	6000	35	25
7.2-30	-	96 A8	6	TT	35	W6	46	43	7	129	20	1560	41	25
9.5-30	-	111 A8	6	TT	39	W7	69	47	10	141	22	2400	41	25
14.9-30	-	127 A8	8	TT	45	W13	140	56	15	167	26	3850	26	25



SIZES ADDED

Size	ALT Size	LI/SI	Ply/*	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)	Psi	Max Speed (mph)
16.9-30	-	137 A8	8	TT	47	W15L	171	58	17	175	27	5070	24	25
16.9-30	-	144 A8	12	TT	47	W15L	187	58	17	175	27	6170	36	25
16.9-30	-	146 A8	14	TT	47	W15L	190	58	17	175	27	6610	41	25
18.4-30	-	139 A8	8	TT	48	W16L	188	61	18	183	28	5350	20	25
18.4-30	-	152 A8	14	TT	48	W16L	228	61	18	183	28	7820	39	25
18.4-30	-	154 A8	16	TT	48	W16L	235	61	18	183	28	8260	42	25
8.3-32	-	107 A8	8	TT	39	W7	57	47	8	141	22	2150	46	25
9.5-32	-	106 A8	6	TT	39	W7	72	49	10	147	23	2090	30	25
12.4-32	-	125 A8	8 8	TT	43	W11	107	54	12	160	25	3630	32	25
16.9-34	-	139 A8	8	TT	47	W15L	191	62	17	187	29	5350	24	25
18.4-34	-	142 A8	14	TT	48	W16L	216	65	18	195	30	5840	20	25
18.4-34	-	153 A8	8	TT	48	W16L	228	65	18	195	30	8040	36	25
12.4-36	-	126 A8	8	TT	43	W11L	117	58	12	172	27	3740	32	25
13.6-36	-	129 A8	12	TT	45	W12	141	60	14	178	28	4070	28	25
13.6-36	-	138 A8	8	TT	45	W12	157	60	14	178	28	5200	46	25
13.6-38	-	131 A8	10	TT	45	W12	148	62	14	184	29	4300	29	25
13.6-38	-	136 A8	8	TT	45	W12	163	62	14	184	29	4930	36	25
15.5-38	-	133 A8	10	TT	42	W14L	165	62	16	185	29	4540	26	25
15.5-38	-	138A6	12	TT	42	W14L	171	62	16	186	29	5200	33	19
15.5-38	-	141A6	8	TT	42	W14L	180	62	16	186	29	5670	41	19
16.9-38	-	141 A8	14	TT	47	W15L	207	66	17	199	31	5670	24	25
16.9-38	-	151 A8	8	TT	47	W15L	222	66	17	199	31	7600	38	25
18.4-38	-	143 A8	14	TT	48	W16L	241	69	18	207	32	6000	20	25
18.4-38	-	155 A8		TT	48	W16L	261	69	18	207	32	8540	38	25