



- Optimized lug distribution to support excellent traction and self-cleaning for puddling operation
- Better inner volume to give higher traction in wet & moist soil conditions
- Good lateral traction gives operational stability



Size	ALT Size	LI/SI	Ply/*	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)	Psi	Max Speed (mph)
5-12	-	64A6/60A8	6	TT	34	4JA	15	21	5	62	10	620	51	19
6-12	-	71A6/67A8	6	TT	34	5JA	19	23	6	68	10	760	38	19
6-14	-	66A6/63A8	4	TL	34	5JA	21	25	6	74	11	660	28	19
9.5-18	-	105A6/101A8	8	TT	57	W8	60	35	10	106	16	2040	44	19
8.3-20	-	101A6/98A8	8	TT	56	W7	50	35	8	105	16	1820	46	19
9.5-20	-	107A6/103A8	8	TT	57	W8	63	38	10	112	17	2150	41	19
9.5-24	-	111A6/108A8	8	TT	56	W8	74	41	9	124	19	2400	41	19
12.4-24	-	120A6/117A8	8	TT	65	W11	111	46	12	137	21	3080	33	19
12.4-28	-	131A6/127A8	12	TT	65	W11	129	50	12	148	23	4290	51	19
13.6-28	-	134A6/130A8	12	TT	68	W12	156	52	14	154	24	4660	44	19
14.9-28	-	137A6/133A8	12	TT	71	W13	176	54	15	161	25	5060	38	19
16.9-28	-	143A6/139A8	12	TT	73	W15L	216	57	17	170	26	6000	35	19