

PRODUCT DATA SHEET

TDB 123

Tyre Construction: Bias

Type: Tube Type / Tubeless

Main Applications: Tractor

TRA Code: R-1



Salient Features:

Unique 23 Degree Lug Design:

- Excellent ground contact.
- Unbeatable traction.

Strong Nylon Carcass:

- Safeguards the tyre against failures.

Special Tread Compound:

- Ensures longer tyre life.



Technical Data



Size	Rim	Unloaded Dimension		Static Load Radius	Rolling Circumference	LI/SI or PR	Inflation Pressure	Recommended load, kg (lbs)							
								Speed, km/h (mph)							
		SW	OD					Field operation			Road Operation; Not high and Sustained Torque				
								High Torque	Low Torque		Static	10	20	30	40
		mm	mm					mm	mm	Bar					
		inch	inch					inch	inch	Psi	6	6	12		
23.1-26*	DW20	587	1605	720	4801	16PR	2.3	4680	6560	5380	10060	6560	5380	4680	4375
		23.1	63.2	28.3	189.0	159 A8	33	10310	14460	11860	22170	14460	11860	10310	9640
23.1-26**		587	1605	720	4801	12PR	1.7	3910	5480	4490	8400	5480	4490	3910	3650
23.1		63.2	28.3	189.0	153 A8	25	8620	12080	9900	18510	12080	9900	8620	8040	
20.8-38	W18A	528	1834	841	5486	8PR	1.3	3370	4730	3870	7250	4730	3870	3370	3150
		20.8	72.2	33.1	216.0	148 A8	19	7430	10420	8530	15980	10420	8530	7430	6940
20.8-38**		528	1834	841	5486	14PR	2.3	4680	6560	5380	10060	6560	5380	4680	4375
		20.8	72.2	33.1	216.0	159 A8	33	10310	14460	11860	22170	14460	11860	10310	9640

Note: The Sizes marked in * are in TL & Sizes marked in ** are in TT/TL

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

