



SIZE ADDED

Optimum Tread Design:

Maximum performance in the field and on-road operations

First in the Industry with Dual Mud Breakers:

Ensure better self-cleaning

Greater Lug Overlap:

Provides safe and comfortable ride at high speeds



STEEL BELTED

Size	ALT Size	LI/SI	Ply/*	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)	Psi	Max Speed (mph)
420/65R20	-	135D	-	TL	48	W13	134	42	17	125	19	4800	35	40
440/65R20	-	138D	-	TL	56	W14L	148	43	18	128	19	5200	35	40
440/65R24	-	135 D	-	TL	56	W14L	169	47	17	139	21	4806	35	40
480/65R24	-	140 D	-	TL	59	W15L	199	49	19	145	22	5511	35	40
540/65R24	-	146 D	-	TL	63	W16L	244	52	21	154	23	6614	35	40
440/65R28	-	138 D	-	TL	56	W14L	185	51	17	151	23	5200	35	40
480/65R28	-	142 D	-	TL	59	W15L	219	53	19	157	24	5842	35	40
540/65R28	-	149 D	-	TL	63	W16L	271	56	21	166	25	7165	35	40
540/65R30	-	150 D	-	TL	63	W16L	285	58	21	176	26	7385	35	40
540/65R34	-	152 D	-	TL	63	W16L	309	62	21	184	28	7826	35	40
600/65R34	-	157 D	-	TL	69	DW20B	390	65	24	194	30	9094	35	40
540/65R38	-	153 D	-	TL	63	W16L	338	66	21	196	30	8047	35	40
600/65R38	-	159 D	-	TL	69	DW20B	421	69	24	205	32	9645	35	40
650/65R38	-	163 D	-	TL	74	DW20B	488	71	25	213	33	107471	35	40
650/65R38 (SB)	-	171 D	-	TL	74	DW20B	525	71	25	213	33	13550	52	40
650/65R42	-	165 D	-	TL	74	DW20B	530	75	25	229	35	11354	35	40