



SIZES ADDED

Tractor Tires Designed with a Unique Mud Breaker:

- Low soil compaction
- High traction
- Excellent driving experience

STEEL BELTED



Size	ALT Size	LI/SI	Ply/*	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)	Psi	Max Speed (mph)
360/70R20	-	129 D	-	TL	52	W11	111	41	14	123	19	4070	35	40
380/70R20	-	122 D	-	TL	52	W12	125	43	15	127	19	3300	23	40
320/70R24	-	116 D	-	TL	51	W10	105	43	13	129	20	2760	23	40
360/70R24	-	122 D	-	TL	52	W11	135	45	14	136	21	3310	23	40
380/70R24	-	125 D	-	TL	52	W12	145	47	15	140	21	3640	23	40
420/70R24	-	130 D	-	TL	56	W13	178	49	16	147	22	4190	23	40
480/70R24	-	138 D	-	TL	61	W15L	220	52	19	155	24	5200	23	40
360/70R28	-	125 D	-	TL	52	W11	150	49	14	147	23	3640	23	40
380/70R28	-	127 D	-	TL	52	W12	162	51	15	152	23	3860	23	40
420/70R28	-	133 D	-	TL	56	W13	195	53	16	159	24	4540	23	40
480/70R28	-	140 D	-	TL	61	W15L	245	56	19	167	26	5510	23	40
420/70R30	-	134 D	-	TL	56	W13	211	55	16	165	25	4670	23	40
480/70R30	-	141 D	-	TL	61	W15L	257	58	19	174	27	5680	23	40
480/70R34	-	143 D	-	TL	61	W15L	283	62	19	186	29	6010	23	40
480/70R34 (SB), (SG)	-	157 D	-	TL	63	W15L	318	62	19	187	29	9090	52	40
520/70R34	-	148 D	-	TL	68	W16L	331	65	20	193	30	6940	23	40
480/70R38	-	145 D	-	TL	61	W15L	308	66	19	198	31	6390	23	40
520/70R38	-	150 D	-	TL	68	W16L	364	69	20	206	32	7390	23	40
580/70R38	-	155 D	-	TL	73	DW18L	451	72	23	215	33	8540	23	40
580/70R38(SB)	-	180 D	-	TL	73	DW18L	493	72	23	215	33	8540	80	40

(SB) - Steel Belted (SG) - Stubble Gaurd