



SIZES ADDED

Tractor Tires Designed with a Unique Mud Breaker:

- Low soil compaction
- High traction
- Excellent driving experience

STEEL BELTED



Size	ALT Size	LI/SI	Ply/*	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)	Psi	Max Speed (mph)
280/85R20	11.2R20	116 D	-	TL	48	W10	81	39	11	116	18	2750	28	40
320/85R20	12.4R20	119 D	-	TL	52	W11	102	41	13	124	19	3000	23	40
250/85R24	9.5R24	109 D	-	TL	48	W8	81	41	10	122	19	2270	23	40
280/85R24	11.2R24	115 D	-	TL	51	W10	95	43	11	127	20	2680	23	40
320/85R24	12.4R24	122 D	-	TL	52	W11	117	45	13	136	21	3300	23	40
340/85R24	13.6R24	125 D	-	TL	54	W12	135	47	14	140	21	3630	23	40
380/85R24	14.9R24	131 D	-	TL	56	W12	162	49	16	148	22	4300	23	40
420/85R24	16.9R24	137 D	-	TL	58	W15L	205	52	17	156	24	5070	23	40
280/85R28	11.2R28	118 D	-	TL	51	W10	107	47	11	140	22	2910	23	40
320/85R28	12.4R28	124 D	-	TL	52	W11	131	49	13	148	23	3520	23	40
340/85R28	13.6R28	127 D	-	TL	54	W12	150	51	14	152	23	3850	23	40
380/85R28	14.9R28	133 D	-	TL	56	W12	182	53	16	160	24	4540	23	40
420/85R28	16.9R28	139 D	-	TL	58	W15L	227	56	17	168	26	5350	23	40
380/85R30	14.9R30	135 D	-	TL	56	W12	197	55	15	166	26	4806	23	40
420/85R30	16.9R30	140 D	-	TL	58	W15L	235	58	17	174	27	5510	23	40
460/85R30	18.4R30	145 D	-	TL	62	W16L	286	61	19	182	28	6390	23	40
320/85R32	12.4R32	126 D	-	TL	52	W11	149	53	13	160	25	3740	23	40
320/85R32 (SB)	12.4R32	145 D	-	TL	52	W11	167	54	13	160	25	6390	64	40
380/85R34	14.9R34	137 D	-	TL	56	W12	214	59	15	178	28	5071	23	40
420/85R34	16.9R34	142 D	-	TL	58	W15L	258	62	17	186	29	5840	23	40
420/85R34 (SB) (SG)	16.9R34	147 D	-	TL	58	W15L	291	62	17	187	29	7820	44	40
460/85R34	18.4R34	152 D	-	TL	62	W16L	299	65	19	194	30	6770	23	40
320/85R36	12.4R36	128 D	-	TL	52	W11	164	57	13	172	27	3960	23	40
320/85R36	12.4R36	148 D	-	TL	52	W11	173	57	13	172	27	6944.6	67	40
340/85R36	13.6R36	132 D	-	TL	54	W12	186	59	14	176	27	4410	23	40
320/85R38	12.4R38	143 D	-	TL	52	W11	177	59	13	178	28	6000	52	40
340/85R38	13.6R38	133 D	-	TL	54	W12	192	61	14	182	28	4540	23	40
420/85R38	16.9R38	144 D	-	TL	58	W15L	278	66	17	198	31	6170	23	40

(SB) - Steel Belted (SG) - Stubble Gaurd



SIZES ADDED

STEEL BELTED

Size	ALT Size	LI/SI	Ply/*	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)	Psi	Max Speed (mph)
460/85R38	18.4R38	149 D	-	TL	62	W16L	327	69	19	206	32	7160	23	40
520/85R38	20.8R38	155 D	-	TL	68	W16L	426	73	21	218	33	8540	23	40
520/85R42	20.8R42	157 D	-	TL	68	DW16L	431	77	21	230	35	9090	23	40
520/85R42	20.8R42	165 D	-	TL	68	DW16L	150	77	20	230	35	11340	41	40
520/85R46	20.8R46	158 D	-	TL	68	DW16L	493	81	21	242	37	9360	23	40
520/85R46	20.8R 46	169 D	-	TL	68	DW16L	550	81	20	242	37	12780	46	40

(SB) - Steel Belted (SG) - Stubble Gaurd