



### Wider Center Rib:

Ease in steering and prevents damage to the grassland

### High Strength Nylon Carcass:

Provides stability to the machine and ensures durability

### Special Tread Compound:

- Provides longer tire life
- Resistance to puncture



Size	ALT Size	LI/SI	Ply/*	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)	Psi	Max Speed (mph)
5.00-15	-	76 A8	6	TT	14	4.00E	14	26	5	78	12	880	60	25
5.50-16	-	82 A8	6	TT	19	4.00E	18	28	6	84	13	1050	56	25
6.00-16	-	85 A8	6	TT	22	4.50E	20	29	6	87	13	1130	52	25
6.00-16	-	91 A8	8	TT	22	4.50E	20	29	6	87	13	1350	68	25
6.50-16	-	88 A8	6	TT	23	4.50E	24	30	7	90	14	1230	48	25
7.50-16	-	99 A8	8	TT	26	5.50F	34	32	8	95	15	1710	56	25
7.50-16	-	104 A8	10	TT	26	5.50F	35	32	8	95	15	1980	69	25
9.00-16	-	111 A8	10	TT	30	6.00F	49	34	9	101	15	2400	60	25
10.00-16	-	115 A8	10	TT	34	W8L	55	35	11	105	16	2680	49	25
11.00-16	-	118 A8	10	TT	37	W10L	70	38	12	114	17	2910	48	25
7.50-18	-	102 A8	8	TT	26	5.50F	35	34	8	101	16	1870	56	25
4.00-19	-	69 A8	4	TT	14	3.00D	13	28	4	84	13	720	52	25
6.00-19	-	89 A8	6	TT	20	4.50E	22	32	6	96	15	1280	52	25
7.50-20	-	105 A8	8	TT	26	5.50F	40	36	8	107	17	2040	56	25