



**Unique Dumbbell Pattern:**

Reduces block tearing and shoulder block deformation

**Strong Nylon Carcass:**

Provides stability to the machine and ensures durability

**Special Tread Compound:**

- Ensures longer tire life
- Resistance to puncture



Size	ALT Size	LI/SI	Ply/*	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)	Psi	Max Speed (mph)
4.50-16	-	74 A8	6	TT	13	3.00D	12	26	5	77	12	830	65	25
5.00-16	-	76 A8	6	TT	15	4.00E	14	27	6	80	13	880	61	25
5.50-16	-	82 A8	6	TT	17	4.00E	17	28	6	84	13	1050	56	25
6.00-16	-	91 A8	8	TT	18	4.50E	25	29	6	87	13	1350	65	25
6.50-16	-	94 A8	8	TT	22	4.50E	28	30	7	90	14	1480	61	25
7.50-16	-	99 A8	8	TT	26	5.50F	36	32	8	95	15	1710	56	25
7.50-18	-	102 A8	8	TT	26	5.50F	38	34	8	101	16	1870	56	25
6.00-19	-	91 A8	8	TT	18	4.50E	23	32	7	96	15	1350	56	25
6.50-20	-	93 A8	8	TT	22	4.50F	36	34	7	102	16	1430	56	25
7.50-20	-	105 A8	8	TT	26	5.50F	44	36	8	107	17	2040	56	25