

PRODUCT DATA SHEET

VDR 900

Tyre Construction: Radial

Type: Tubeless

Main Applications: Sprayer & Tractor

TRA Code: R-1W



Salient Features:

- Built to handle 40% more load than a conventional radial tire, or the same load at 40% lower pressure.
- VF tires with stronger lugs with larger Contact Patch gives Excellent traction with self-cleaning characteristics which decreases slippage, delivers lower fuel consumption, and increases overall productivity.
- Steel Belts offers Puncture Protection and distributes uniform ground pressure which helps less soil compaction and less crop damage.
- Reinforced sidewalls and bead zones offer increased casing stiffness to carry extra load.
- The more radially stiffer tyre makes it possible to transition from field to road and vice versa without adjusting the pressure. At the reduced pressure required for field use, the tyre can also run at full speed on the road yet deliver the same fuel efficiencies as a standard tyre at road pressure.



Technical Data



| Size | Rim | Unloaded Dimension | | Static Load Radius | Rolling Circumference | PR & LI/SI | Inflation Pressure | Recommended load (kg) (lbs) | | | | | |
|-------------------|-------|--------------------|------|--------------------|-----------------------|------------|--------------------|-----------------------------|-------|-------|-------|-------|-------|
| | | SW | OD | | | | | Speed (kmph) (mph) | | | | | |
| | | mm | mm | mm | mm | | bar | 10 | 25 | 30 | 40 | 50 | 65 |
| | | inch | inch | inch | inch | | Psi | 6 | 16 | 19 | 25 | 31 | 40 |
| VF 580/85R42 (SB) | DW20B | 595 | 2040 | 935 | 6126 | 183 D | 1.0 | 5430 | 5090 | 5040 | 4940 | 4940 | 4940 |
| | | | | | | | 15 | 11960 | 11210 | 11100 | 10880 | 10880 | 10880 |
| | | | | | | | 1.2 | 6110 | 5720 | 5660 | 5550 | 5550 | 5550 |
| | | | | | | | 17 | 13460 | 12600 | 12470 | 12220 | 12220 | 12220 |
| | | | | | | | 1.6 | 7470 | 6990 | 6930 | 6790 | 6790 | 6790 |
| | | | | | | | 23 | 16450 | 15400 | 15260 | 14960 | 14960 | 14960 |
| | 23.4 | 80.3 | 36.8 | 241.2 | 2.0 | | 8200 | 7670 | 7600 | 7450 | 7450 | 7450 | |
| | | | | | 29 | | 18060 | 16890 | 16740 | 16410 | 16410 | 16410 | |
| | | | | | 2.4 | | 8720 | 8170 | 8090 | 7930 | 7930 | 7930 | |
| | | | | | 35 | | 19210 | 18000 | 17820 | 17470 | 17470 | 17470 | |
| | | | | | 2.8 | | 9630 | 9010 | 8930 | 8750 | 8750 | 8750 | |
| | | | | | 41 | | 21210 | 19850 | 19670 | 19270 | 19270 | 19270 | |
| VF 380/90R46 (SB) | W13 | 383 | 1852 | 866 | 5561 | 173 D | 1.0 | 3120 | 2930 | 2900 | 2840 | 2840 | 2840 |
| | | | | | | | 15 | 6870 | 6450 | 6390 | 6260 | 6260 | 6260 |
| | | | | | | | 1.6 | 4290 | 4020 | 3980 | 3900 | 3900 | 3900 |
| | | | | | | | 23 | 9450 | 8850 | 8770 | 8590 | 8590 | 8590 |
| | | | | | | | 2.0 | 4710 | 4410 | 4370 | 4280 | 4280 | 4280 |
| | | | | | | | 29 | 10370 | 9710 | 9630 | 9430 | 9430 | 9430 |
| | | | | | | | 2.4 | 5020 | 4700 | 4650 | 4560 | 4560 | 4560 |
| | | | | | | | 35 | 11060 | 10350 | 10240 | 10040 | 10040 | 10040 |
| | | | | | | | 2.8 | 5500 | 5150 | 5100 | 5000 | 5000 | 5000 |
| | 15.1 | 72.9 | 34.1 | 219.0 | 41 | | 12110 | 11340 | 11230 | 11010 | 11010 | 11010 | |
| | | | | | 3.2 | | 5930 | 5550 | 5500 | 5390 | 5390 | 5390 | |
| | | | | | 46 | | 13060 | 12220 | 12110 | 11870 | 11870 | 11870 | |
| | | | | | 3.6 | | 6330 | 5920 | 5870 | 5750 | 5750 | 5750 | |
| | | | | | 52 | | 13940 | 13040 | 12930 | 12670 | 12670 | 12670 | |
| | | | | | 4.0 | | 6670 | 6240 | 6180 | 6060 | 6060 | 6060 | |
| | | | | | 58 | | 14690 | 13740 | 13610 | 13350 | 13350 | 13350 | |
| | | | | | 4.4 | | 7150 | 6700 | 6630 | 6500 | 6500 | 6500 | |
| | | | | | 64 | | 15750 | 14760 | 14600 | 14320 | 14320 | 14320 | |

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com



Technical Data



| Size | Rim | Unloaded Dimension | | Static Load Radius | Rolling Circumference | PR & LI/SI | Inflation Pressure | Recommended load (kg) (lbs) | | | | | | |
|-------------------|-------|--------------------|-------|--------------------|-----------------------|------------|--------------------|-----------------------------|-------|-------|-------|-------|------|--|
| | | SW | OD | | | | | Speed (kmph) (mph) | | | | | | |
| | | mm | mm | | | | | 10 | 25 | 30 | 40 | 50 | 65 | |
| | | inch | inch | | | | | 6 | 16 | 19 | 25 | 31 | 40 | |
| VF 520/85R46 (SB) | DW18L | 530 | 2052 | 949 | 6162 | 173 D | 1.0 | 4760 | 4460 | 4420 | 4330 | 4330 | 4330 | |
| | | | | | | | 15 | 10480 | 9820 | 9740 | 9540 | 9540 | 9540 | |
| | | 1.2 | 5360 | 5020 | 4970 | | 4870 | 4870 | 4870 | | | | | |
| | | 17 | 11810 | 11060 | 10950 | | 10730 | 10730 | 10730 | | | | | |
| | 20.9 | 80.8 | 37.4 | 242.6 | 1.6 | | 6560 | 6140 | 6080 | 5960 | 5960 | 5960 | | |
| | | | | | 23 | | 14450 | 13520 | 13390 | 13130 | 13130 | 13130 | | |
| | | | | | 2 | | 7150 | 6700 | 6630 | 6500 | 6500 | 6500 | | |
| | | | | | 29 | | 15750 | 14760 | 14600 | 14320 | 14320 | 14320 | | |
| VF 320/90R50 (SB) | W11 | 323 | 1846 | 873 | 5543 | 169 D | 1.0 | 2540 | 2380 | 2360 | 2310 | 2310 | 2310 | |
| | | | | | | | 15 | 5590 | 5240 | 5200 | 5090 | 5090 | 5090 | |
| | | | | | | | 1.6 | 3490 | 3270 | 3230 | 3170 | 3170 | 3170 | |
| | | | | | | | 23 | 7690 | 7200 | 7110 | 6980 | 6980 | 6980 | |
| | | 12.7 | 72.7 | 34.4 | 218.2 | | 2.0 | 3830 | 3580 | 3550 | 3480 | 3480 | 3480 | |
| | | | | | | | 29 | 8440 | 7890 | 7820 | 7670 | 7670 | 7670 | |
| | | | | | | | 2.4 | 4080 | 3820 | 3780 | 3710 | 3710 | 3710 | |
| | | | | | | | 35 | 8990 | 8410 | 8330 | 8170 | 8170 | 8170 | |
| | 2.8 | | | | | | 4470 | 4180 | 4140 | 4060 | 4060 | 4060 | | |
| | 41 | | | | | | 9850 | 9210 | 9120 | 8940 | 8940 | 8940 | | |
| | 3.6 | | | | | | 5140 | 4810 | 4760 | 4670 | 4670 | 4670 | | |
| | 52 | | | | | | 11320 | 10590 | 10480 | 10290 | 10290 | 10290 | | |
| | 4.4 | 5890 | 5510 | 5460 | 5350 | | 5350 | 5350 | | | | | | |
| | 64 | 12970 | 12140 | 12030 | 11780 | | 11780 | 11780 | | | | | | |
| | 4.8 | 6380 | 5970 | 5920 | 5800 | | 5800 | 5800 | | | | | | |
| | 70 | 14050 | 13150 | 13040 | 12780 | | 12780 | 12780 | | | | | | |

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com



Technical Data



| Size | Rim | Unloaded Dimension | | Static Load Radius | Rolling Circumference | LI/SI | Inflation Pressure | Recommended load (kg) (lbs) | | | | | |
|--------------------------|-------|--------------------|-------|--------------------|-----------------------|-------|--------------------|-----------------------------|-------|-------|-------|-------|-------|
| | | SW | OD | | | | | Speed (kmph) (mph) | | | | | |
| | | mm | mm | | | | | 10 | 25 | 30 | 40 | 50 | 65 |
| | | inch | inch | | | | | inch | inch | inch | inch | inch | inch |
| VF 380/90R50 (SB) | W13 | 383 | 1954 | 917 | 5868 | 175 D | 1 | 3270 | 3060 | 3030 | 2970 | 2970 | 2970 |
| | | | | | | | 15 | 7200 | 6740 | 6670 | 6540 | 6540 | 6540 |
| | | | | | | | 1.6 | 4490 | 4200 | 4160 | 4080 | 4080 | 4080 |
| | | | | | | | 23 | 9890 | 9250 | 9160 | 8990 | 8990 | 8990 |
| | | | | | | | 2 | 4920 | 4600 | 4560 | 4470 | 4470 | 4470 |
| | | | | | | | 29 | 10840 | 10130 | 10040 | 9850 | 9850 | 9850 |
| | | | | | | | 2.4 | 5250 | 4910 | 4870 | 4770 | 4770 | 4770 |
| | 35 | 11560 | 10810 | 10730 | 10510 | | 10510 | 10510 | | | | | |
| | 2.8 | 5740 | 5380 | 5320 | 5220 | | 5220 | 5220 | | | | | |
| | 41 | 12640 | 11850 | 11720 | 11500 | | 11500 | 11500 | | | | | |
| | 3.2 | 6190 | 5800 | 5740 | 5630 | | 5630 | 5630 | | | | | |
| | 46 | 13630 | 12780 | 12640 | 12400 | | 12400 | 12400 | | | | | |
| | 3.6 | 6610 | 6190 | 6130 | 6010 | | 6010 | 6010 | | | | | |
| | 52 | 14560 | 13630 | 13500 | 13240 | | 13240 | 13240 | | | | | |
| 4.4 | 7590 | 7110 | 7040 | 6900 | 6900 | 6900 | | | | | | | |
| 64 | 16720 | 15660 | 15510 | 15200 | 15200 | 15200 | | | | | | | |
| VF 380/105R50 (SB) | W13 | 383 | 2068 | 964 | 6210 | 179 D | 1.0 | 3700 | 3460 | 3430 | 3360 | 3360 | 3360 |
| | | | | | | | 15 | 8150 | 7620 | 7560 | 7400 | 7400 | 7400 |
| | | | | | | | 1.6 | 5080 | 4760 | 4710 | 4620 | 4620 | 4620 |
| | | | | | | | 23 | 11190 | 10480 | 10370 | 10180 | 10180 | 10180 |
| | | | | | | | 2.0 | 5590 | 5230 | 5180 | 5080 | 5080 | 5080 |
| | | | | | | | 29 | 12310 | 11520 | 11410 | 11190 | 11190 | 11190 |
| | | | | | | | 2.4 | 5950 | 5570 | 5520 | 5410 | 5410 | 5410 |
| | 35 | 13110 | 12270 | 12160 | 11920 | | 11920 | 11920 | | | | | |
| | 2.8 | 6510 | 6100 | 6040 | 5920 | | 5920 | 5920 | | | | | |
| | 41 | 14340 | 13440 | 13300 | 13040 | | 13040 | 13040 | | | | | |
| | 3.2 | 7030 | 6580 | 6520 | 6390 | | 6390 | 6390 | | | | | |
| | 46 | 15480 | 14490 | 14360 | 14070 | | 14070 | 14070 | | | | | |
| | 3.6 | 7490 | 7010 | 6950 | 6810 | | 6810 | 6810 | | | | | |
| | 52 | 16500 | 15440 | 15310 | 15000 | | 15000 | 15000 | | | | | |
| 4 | 7900 | 7400 | 7320 | 7180 | 7180 | 7180 | | | | | | | |
| 58 | 17400 | 16300 | 16120 | 15810 | 15810 | 15810 | | | | | | | |
| 4.4 | 8530 | 7980 | 7910 | 7750 | 7750 | 7750 | | | | | | | |
| 64 | 18790 | 17580 | 17420 | 17070 | 17070 | 17070 | | | | | | | |

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com



Technical Data



| Size | Rim | Unloaded Dimension | | Static Load Radius | Rolling Circumference | LI/SI | Inflation Pressure | Recommended load (kg) (lbs) | | | | | |
|-------------------------|-------|--------------------|------|--------------------|-----------------------|-------|--------------------|-----------------------------|-------|-------|-------|-------|-------|
| | | SW | OD | | | | | Speed (kmph) (mph) | | | | | |
| | | mm | mm | | | | | 10 | 25 | 30 | 40 | 50 | 65 |
| | | inch | inch | | | | | 6 | 16 | 19 | 25 | 31 | 40 |
| VF 420/95R50 (SB) | W14L | 419 | 2068 | 964 | 6210 | 177 D | 1.0 | 3960 | 3710 | 3670 | 3600 | 3600 | 3600 |
| | | | | | | | 15 | 8720 | 8170 | 8080 | 7930 | 7930 | 7930 |
| | | | | | | | 1.6 | 5430 | 5090 | 5040 | 4940 | 4940 | 4940 |
| | | | | | | | 23 | 11960 | 11210 | 11100 | 10880 | 10880 | 10880 |
| | | | | | | | 2.0 | 5970 | 5590 | 5540 | 5430 | 5430 | 5430 |
| | | | | | | | 29 | 13150 | 12310 | 12200 | 11960 | 11960 | 11960 |
| | | | | | | | 2.4 | 6360 | 5950 | 5900 | 5780 | 5780 | 5780 |
| | 15.1 | 16.1 | 17.1 | 18.1 | 35 | | 14010 | 13110 | 13000 | 12730 | 12730 | 12730 | |
| | | | | | 2.8 | | 6960 | 6520 | 6460 | 6330 | 6330 | 6330 | |
| | | | | | 41 | | 15330 | 14360 | 14230 | 13940 | 13940 | 13940 | |
| | | | | | 3.2 | | 7510 | 7030 | 6970 | 6830 | 6830 | 6830 | |
| | | | | | 46 | | 16540 | 15480 | 15350 | 15040 | 15040 | 15040 | |
| | | | | | 3.6 | | 8030 | 7520 | 7450 | 7300 | 7300 | 7300 | |
| | | | | | 52 | | 17690 | 16560 | 16410 | 16080 | 16080 | 16080 | |
| VF 480/80R50 (SB) | DW16L | 479 | 2038 | 952 | 6120 | 179 D | 1 | 4180 | 3910 | 3880 | 3800 | 3800 | 3800 |
| | | | | | | | 15 | 9210 | 8610 | 8550 | 8370 | 8370 | 8370 |
| | | | | | | | 1.6 | 5750 | 5390 | 5330 | 5230 | 5230 | 5230 |
| | | | | | | | 23 | 12670 | 11870 | 11740 | 11520 | 11520 | 11520 |
| | | | | | | | 2 | 6310 | 5910 | 5850 | 5740 | 5740 | 5740 |
| | | | | | | | 29 | 13900 | 13020 | 12890 | 12640 | 12640 | 12640 |
| | | | | | | | 2.4 | 6720 | 6290 | 6230 | 6110 | 6110 | 6110 |
| | 18.9 | 80.2 | 37.5 | 240.9 | 35 | | 14800 | 13850 | 13720 | 13460 | 13460 | 13460 | |
| | | | | | 2.8 | | 7370 | 6900 | 6830 | 6700 | 6700 | 6700 | |
| | | | | | 41 | | 16230 | 15200 | 15040 | 14760 | 14760 | 14760 | |
| | | | | | 3.2 | | 7950 | 7450 | 7370 | 7230 | 7230 | 7230 | |
| | | | | | 46 | | 17510 | 16410 | 16230 | 15930 | 15930 | 15930 | |
| | | | | | 3.6 | | 8530 | 7980 | 7910 | 7750 | 7750 | 7750 | |
| | | | | | 52 | | 18790 | 17580 | 17420 | 17070 | 17070 | 17070 | |

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com



Technical Data



| Size | Rim | Unloaded Dimension | | Static Load Radius | Rolling Circumference | LI/SI | Inflation Pressure | Recommended load (kg) (lbs) | | | | | |
|----------------------|-------|--------------------|-------|--------------------|-----------------------|-------|--------------------|-----------------------------|-------|-------|-------|-------|-------|
| | | SW | OD | | | | | Speed (kmph) (mph) | | | | | |
| | | mm | mm | | | | | 10 | 25 | 30 | 40 | 50 | 65 |
| | | inch | inch | | | | | bar | Psi | 6 | 16 | 19 | 25 |
| VF 480/95R50 (SB) | DW16L | 479 | 2182 | 1011 | 6552 | 176 D | 1.0 | 4830 | 4520 | 4480 | 4390 | 4390 | 4390 |
| | | | | | | | 15 | 10640 | 9960 | 9870 | 9670 | 9670 | 9670 |
| | | | | | | | 1.6 | 6640 | 6220 | 6160 | 6040 | 6040 | 6040 |
| | | | | | | | 23 | 14630 | 13700 | 13570 | 13300 | 13300 | 13300 |
| | | 18.9 | 85.9 | 39.8 | 258.0 | | 2.0 | 7290 | 6830 | 6760 | 6630 | 6630 | 6630 |
| | | | | | | | 29 | 16060 | 15040 | 14890 | 14600 | 14600 | 14600 |
| | | | | | | | 2.4 | 7810 | 7310 | 7240 | 7100 | 7100 | 7100 |
| | | | | | | | 35 | 17200 | 16100 | 15950 | 15640 | 15640 | 15640 |
| VF 250/115R54 (SB) # | W8 | 250 | 1947 | 923 | 5847 | 151 D | 1.0 | 2240 | 2100 | 2080 | 2040 | 2040 | 2040 |
| | | | | | | | 15 | 4930 | 4630 | 4580 | 4490 | 4490 | 4490 |
| | | | | | | | 1.6 | 3080 | 2880 | 2860 | 2800 | 2800 | 2800 |
| | | | | | | | 23 | 6780 | 6340 | 6300 | 6170 | 6170 | 6170 |
| | | 9.8 | 76.7 | 36.3 | 230.2 | | 2.0 | 3390 | 3170 | 3140 | 3080 | 3080 | 3080 |
| | | | | | | | 29 | 7470 | 6980 | 6920 | 6780 | 6780 | 6780 |
| | | | | | | | 2.4 | 3610 | 3380 | 3350 | 3280 | 3280 | 3280 |
| | | | | | | | 35 | 7950 | 7440 | 7380 | 7220 | 7220 | 7220 |
| VF 320/90R54 (SB) | W11 | 323 | 1948 | 924 | 5850 | 168 D | 1.0 | 2650 | 2480 | 2460 | 2410 | 2410 | 2410 |
| | | | | | | | 15 | 5840 | 5460 | 5420 | 5310 | 5310 | 5310 |
| | | | | | | | 1.6 | 3640 | 3410 | 3380 | 3310 | 3310 | 3310 |
| | | | | | | | 23 | 8020 | 7510 | 7440 | 7290 | 7290 | 7290 |
| | | | | | | | 2 | 3990 | 3740 | 3700 | 3630 | 3630 | 3630 |
| | | | | | | | 29 | 8790 | 8240 | 8150 | 8000 | 8000 | 8000 |
| | | | | | | | 2.4 | 4260 | 3990 | 3950 | 3870 | 3870 | 3870 |
| | | | | | | | 35 | 9380 | 8790 | 8700 | 8520 | 8520 | 8520 |
| | | 12.7 | 76.7 | 36.4 | 230.3 | | 2.8 | 4660 | 4370 | 4320 | 4240 | 4240 | 4240 |
| | | | | | | | 41 | 10260 | 9630 | 9520 | 9340 | 9340 | 9340 |
| | | | | | | | 3.2 | 5030 | 4710 | 4660 | 4570 | 4570 | 4570 |
| | | | | | | | 46 | 11080 | 10370 | 10260 | 10070 | 10070 | 10070 |
| | | | | | | | 3.6 | 5360 | 5020 | 4970 | 4870 | 4870 | 4870 |
| | | | | | | | 52 | 11810 | 11060 | 10950 | 10730 | 10730 | 10730 |
| 4.4 | 6160 | 5770 | 5710 | 5600 | 5600 | 5600 | | | | | | | |
| 64 | 13570 | 12710 | 12580 | 12330 | 12330 | 12330 | | | | | | | |

Note: # VF 250/115R54 size replaces VF 230/115R54

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com



Technical Data



Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ▪ **E:** enquiry@ascensotyres.com ▪ **W:** www.ascensotyres.com



Technical Data



| Size | Rim | Unloaded Dimension | | Static Load Radius | Rolling Circumference | LI/SI | Inflation Pressure | Recommended load (kg) (lbs) | | | | | |
|--------------------------|-------|--------------------|-------|--------------------|-----------------------|-------|--------------------|-----------------------------|-------|-------|-------|-------|-------|
| | | SW | OD | | | | | Speed (kmph) (mph) | | | | | |
| | | mm | mm | | | | | 10 | 25 | 30 | 40 | 50 | 65 |
| | | inch | inch | | | | | bar | Psi | 6 | 16 | 19 | 25 |
| VF 380/90R54 (SB) | W13 | 383 | 2056 | 968 | 6174 | 176 D | 1.0 | 3400 | 3180 | 3150 | 3090 | 3090 | 3090 |
| | | | | | | | 15 | 7490 | 7000 | 6940 | 6810 | 6810 | 6810 |
| | | | | | | | 1.6 | 4680 | 4380 | 4340 | 4250 | 4250 | 4250 |
| | | | | | | | 23 | 10310 | 9650 | 9560 | 9360 | 9360 | 9360 |
| | | | | | | | 2.0 | 5130 | 4800 | 4750 | 4660 | 4660 | 4660 |
| | | | | | | | 29 | 11300 | 10570 | 10460 | 10260 | 10260 | 10260 |
| | | | | | | | 2.4 | 5470 | 5120 | 5070 | 4970 | 4970 | 4970 |
| | 35 | 12050 | 11280 | 11170 | 10950 | | 10950 | 10950 | | | | | |
| | 2.8 | 5980 | 5600 | 5550 | 5440 | | 5440 | 5440 | | | | | |
| | 41 | 13170 | 12330 | 12220 | 11980 | | 11980 | 11980 | | | | | |
| | 3.2 | 6460 | 6050 | 5990 | 5870 | | 5870 | 5870 | | | | | |
| | 46 | 14230 | 13330 | 13190 | 12930 | | 12930 | 12930 | | | | | |
| | 3.6 | 6890 | 6450 | 6390 | 6260 | | 6260 | 6260 | | | | | |
| | 52 | 15180 | 14210 | 14070 | 13790 | | 13790 | 13790 | | | | | |
| 4.4 | 7810 | 7310 | 7240 | 7100 | 7100 | 7100 | | | | | | | |
| 64 | 17200 | 16100 | 15950 | 15640 | 15640 | 15640 | | | | | | | |
| VF 380/105R54 (SB) | W13 | 383 | 2163 | 1012 | 6495 | 180 D | 1.0 | 3830 | 3580 | 3550 | 3480 | 3480 | 3480 |
| | | | | | | | 14 | 8440 | 7890 | 7820 | 7670 | 7670 | 7670 |
| | | | | | | | 1.6 | 5260 | 4920 | 4880 | 4780 | 4780 | 4780 |
| | | | | | | | 23 | 11590 | 10840 | 10750 | 10530 | 10530 | 10530 |
| | | | | | | | 2 | 5760 | 5400 | 5340 | 5240 | 5240 | 5240 |
| | | | | | | | 29 | 12690 | 11890 | 11760 | 11540 | 11540 | 11540 |
| | | | | | | | 2.4 | 6140 | 5750 | 5690 | 5580 | 5580 | 5580 |
| | 35 | 13520 | 12670 | 12530 | 12290 | | 12290 | 12290 | | | | | |
| | 2.8 | 6730 | 6300 | 6240 | 6120 | | 6120 | 6120 | | | | | |
| | 41 | 14820 | 13880 | 13740 | 13480 | | 13480 | 13480 | | | | | |
| | 3.2 | 7260 | 6800 | 6730 | 6600 | | 6600 | 6600 | | | | | |
| | 46 | 15990 | 14980 | 14820 | 14540 | | 14540 | 14540 | | | | | |
| | 3.6 | 7740 | 7250 | 7180 | 7040 | | 7040 | 7040 | | | | | |
| | 52 | 17050 | 15970 | 15810 | 15510 | | 15510 | 15510 | | | | | |
| 4 | 8160 | 7640 | 7570 | 7420 | 7420 | 7420 | | | | | | | |
| 58 | 17970 | 16830 | 16670 | 16340 | 16340 | 16340 | | | | | | | |
| 4.4 | 8800 | 8240 | 8160 | 8000 | 8000 | 8000 | | | | | | | |
| 64 | 19380 | 18150 | 17970 | 17620 | 17620 | 17620 | | | | | | | |

Note: VF- Very High Flexion, SB - Steel Belted

Note: All tyres confirm to ETRTO standards

Mahansaria Tyres Pvt. Ltd.

3rd Floor, Peninsula Chambers, Ganpat Rao Kadam Marg, Lower Parel West, Mumbai 400013, India

T: +91 22 4348 1600 ■ E: enquiry@ascensotyres.com ■ W: www.ascensotyres.com

