



Robust Tread Design:

Generates maximum traction and resistance to slippage

Strong Nylon Casing:

- Heavy load-carrying capacity
- Resistance to impacts



Size	ALT Size	LI/SI	Ply/*	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)	Psi	Max Speed (mph)
15.5-25	-	168A2	12	TL	32	12.00/1.3	207	50	16	151	23	12350	58	6
17.5-25	-	177A2	16	TL	34	14.00/1.5	254	53	18	159	24	16060	69	6
17.5-25	-	181A2	20	TL	34	14.00/1.5	291	53	18	159	24	18150	84	6
17.5-25	-	188A2	24	TL	34	14.00/1.5	315	53	18	159	24	22000	102	6
20.5-25	-	181A2	16	TL	38	17.00/2.0	375	59	20	176	26	18150	51	6
20.5-25	-	186A2	20	TL	38	17.00/2.0	375	59	20	176	26	20900	66	6
23.5-25	-	191A2	20	TL	40	19.5/1.5	529	64	24	190	28	23980	55	6
26.5-25	-	203A2	28	TL	44	22.0/3.0	838	69	26	207	31	34100	61	6