



Optimum Tread Design:

Maximum performance in the field and on-road operations

First in the Industry with Dual Mud Breakers:

Ensure better self-cleaning and maximum traction

Greater Lug Overlap:

Provides safe and comfortable ride at high speeds



Size	ALT Size	LI/SI	Ply/*	Type	Tread Depth (32 nds)	Preferred Rim	Wt (lbs)	OD inches	SW inches	RC inches	SLR inches	Max Load (lbs)	Psi	Max Speed (mph)
600/65R28	-	154 D	-	TL	70	DW20B	340	59	24	176	27	8267	35	40
600/70R28	-	161 D	-	TL	70	DW20B	377	61	24	183	28	10196	41	40
600/70R30	-	152 D	-	TL	69	DW20B	377	63	24	189	29	7826	35	40
600/70R34	-	160 D	-	TL	69	DW20B	422	67	24	201	31	9910	35	40
710/70R38	-	172 D	-	TL	75	DW23B	648	77	28	231	35	13889	35	40
710/70R38	-	178 D	-	TL	75	DW23B	674	77	28	231	35	16534	49	40
650/85R38	-	173 D	-	TL	78	DW23B	705	82	27	244	37	14330	35	40
800/70R38	-	178 D	-	TL	78	DW27B	797	82	31	246	37	16534	35	40
620/70R42	-	166 D	-	TL	69	DW20B	511	76	25	228	35	11684	35	40
710/70R42	-	173 D	-	TL	75	DW23B	699	81	28	243	37	14330	35	40
710/75R42	-	175 D	-	TL	77	DW23B	785	84	28	251	38	15212	35	40